




UNSW
Water Research
Laboratory



Physical model testing of breakwater design



UNSW
Water Research
Laboratory

Breakwater design using XBlocPlus – 1.2 m wave flume

Testing of existing vs improved geotextile groyne design



UNSW
SYDNEY

Water
Research
Laboratory
School of Civil and
Environmental Engineering



Existing Groyne

Wave Period: 12 s

Wave Height: 1.8 m

Water Level: 1.55 m AHD



UNSW
Water Research
Laboratory




UNSW
Water Research
Laboratory



Wave deflector being used to reduce overtopping under bore wave condition



UNSW
Water Research
Laboratory



Testing wave pumping forces



UNSW
Water Research
Laboratory



Short crested waves – wave basin



UNSW
Water Research
Laboratory



UNSW
SYDNEY

Water
Research
Laboratory
School of Civil and
Environmental Engineering

Real-time video monitoring of wave overtopping



UNSW
Water Research
Laboratory



Modelling wave overtopping risks to pedestrians

E001 Toe Scour, Design Cond.



UNSW
SYDNEY

Water Research Laboratory



UNSW
Water Research
Laboratory



As modelled versus as built



UNSW
Water Research
Laboratory



UNSW
SYDNEY

Water
Research
Laboratory
School of Civil and
Environmental Engineering

Testing wave uplift pressures on a coastal walkway overhang



UNSW
Water Research
Laboratory



Physical model testing of breakwater design



UNSW
Water Research
Laboratory

Ocean pool research and design



UNSW
Water Research
Laboratory



Physical modelling of a Pacific Island during a cyclone



UNSW
Water Research
Laboratory



Tuvalu reef waves – 0.9 m wave flume



UNSW
Water Research
Laboratory



Ohau Point, New Zealand – 3 m wave flume



UNSW
Water Research
Laboratory



Physical model construction using hanbar armour units



UNSW
Water Research
Laboratory



Stepped seawall design testing – 1.2 m wave flume



UNSW
Water Research
Laboratory

As modelled versus as built